

Tabelle II

der Gewölbestärken für Spannweiten von 1,5 bis 10,00 m
und Belastungen von 100 bis 10 000 kg/qm.

I	1,5 m	2,0 m	2,5 m	3,0 m	3,5 m	4,0 m	4,5 m	5,0 m	6,0 m	7,0 m	8,0 m	9,0 m	10,0 m
p kg/qm	Gewölbestärke in mm												
100	3	4	4	5	6	7	8	9	11	12	14	16	18
250	4	6	7	8	10	11	13	14	17	19	22	25	28
500	6	8	10	12	14	16	18	20	24	28	31	35	39
750	7	10	12	14	17	19	22	24	29	34	39	43	48
1000	8	11	14	17	19	22	25	28	33	39	44	50	56
1250	9	12	16	19	22	25	28	31	37	43	50	56	62
1500	10	14	17	20	24	27	31	34	41	48	54	61	68
1750	11	15	18	22	26	29	33	37	44	51	59	66	74
2000	12	16	20	24	28	31	35	39	47	55	63	71	79
2500	13	18	22	27	31	36	40	44	53	62	70	79	88
3000	14	19	24	29	34	38	43	48	58	67	77	86	96
4000	17	22	28	33	39	44	50	56	67	78	89	100	111
5000	19	25	31	37	43	50	56	62	74	87	99	112	125
6000	20	27	34	41	48	54	61	68	82	95	109	122	136
7000	22	29	37	44	51	58	66	74	88	102	117	132	147
8000	23	31	39	47	55	63	71	79	94	110	126	141	157
9000	25	33	42	50	58	66	75	83	100	116	133	150	167
10000	26	35	44	53	61	72	79	88	105	123	140	158	175

I Spannweite. — p gleichmässig vertheilte Last.

Siehe dazu die Bemerkungen auf Seite 82.